

PL512 Power Supply System

[Request Quote](#)



PL512 Power Supply System



The PL 512 is a high sophisticated, high density, programmable 12-channel floating low-voltage power supply system. Using the remote monitoring and control features either via USB or Ethernet it can be used to supply external load-channels with high power consumption also over long distances. Up to 3kW (3Ubox) DC output power can be provided.

Voltages, currents, temperatures and output power are programmable and controlled by the internal processor. Illegal modes as well as failure conditions will be detected. Dynamic behavior is programmable via USB port (long-moderate-short sensed distances to loads).

The modular construction with a 19" rack mountable power bin and a plug-in power supply box allows to swap the power supply without any tools and within shortest time.

Main Features

- Up to 12 independent potential free low voltage DC outputs, with up to 3 kW output power
- Fully microprocessor controlled, programmable warning and trip levels
- Programmable voltages, current limits, ramping up/down and group behavior
- Sense line compensation or impedance control selectable
- Extremely low noise and ripple

PL512 Features

- Up to 12 independent, potential free DC outputs, 250W each, total up to 3 kW output power
- Extremely low noise and ripple
- Channels can be operated in Master-Slave mode for paralleling of two or more outputs (current boosting).
- Floating range: +/-100V (default, optimal for low noise). Can be increased up to +/- 500V
- Programmable voltages and thresholds on voltages, currents and temperatures, ramp rates, fully controlled, programmable trip levels and action / group behavior , voltage or current controlled mode
- CE conform EN 50 081/82 part 1 (EN 50 022 B), safety in accordance with EN 60 950
- Ethernet and USB interfaces for remote monitoring and control, Web interface / SNMP
- 94V - 265VAC world-wide auto-range AC input, with power factor correction / sinusoidal mains current EN 61000-3-2, CE
- DC Output connections: 4mm (M4-80A), Sense and temperature sensor connections: 9 pin Sub D female connector for 2 channels, senses wired to terminals on rear side.
- Optional alphanumeric display
- Optional with Power fail- and System Reset- Signal
- Optional with Interlock input
- Optional direct water cooling with same size as air cooled ones
- Dimensions: 430mm x 3U (133mm) x 325mm [whd], weight: from 9.6 to 19 kg depending on the number of power modules

PL512 consists of:

=> **Power Bin**: 19" bin for rack mounting hosting a power box

Type	Dimensions	Features
<i>PBN512 – 3U RASO</i>	3U x 19" x 445mm	Folded metal frame
<i>PBN512 – 4U</i>	4U x 19" x 445mm	Aluminum side panels

=> **Power Box** containing a PFC mains input module, a control card and slots for up to 6 modules (MDH/MDL types, dual channel, 250W) for a maximum of 12 channels. The power box includes the Ethernet/USB combo card and can be outfitted with an optional display (**EX version**) as well as individual channel interlock feature (**I option**)

PL512 Power Box for insertion in Power Bin :

Type	Dimensions	Features
<i>PBX512</i>	3U x 19" x 445mm	Ethernet, USB, "Easy Lever" extraction mechanism
<i>PBX506 – EX</i>	3U x 19" x 445mm	Display, Ethernet, USB, "Easy Lever" extraction mechanism

=> **Power Modules** integrated into Power Box for a maximum of 6 modules / 12 channels

Type	Optimal Voltage range	Channels per module	Peak output / Power
<i>MDL – 07/24</i>	7V ... 24V	2	+/- 11,5A / 275W (550W total)
<i>MDH – 02/07</i>	2V ... 7V	2	+/- 30A / 210W (420W total)
<i>MDH – 07/16</i>	7V ... 16V	2	+/- 20A / 250W (500W total)
<i>MDH – 30/60</i>	30V ... 60V	2	+/- 6A / 250W (500W total)

Standard MDH/MDL power modules (up to 6)**Regulation (fast circuit for short sensed distance)****Static:**

MEH 550W/650W	<15mV	+/-100% load, +/- full mains range
MDH (20A)	<0.05%	+/-100% load, +/- full mains range
MDL, MDH	<0.1%	+/-100% load, +/- full mains range

Dynamic (0,5 m wire)

MEH, MDH	<100mV	+/-25% load
MDL, MDH	<0.7%	+/-25% load

Recovery time (0,5 m wire) +/-25% load**within +/-1% deviation****within +/-0.1% dev.**

Modules 550W	0.2ms	0.5ms
Modules 650W >30V	0.5ms	1.0ms
MDL, MDH	0.0ms	1.0ms

Conditions: Current slope <1000A/ms, 20mF per 100A parallel to load

Regulation (slow circuit for long sensed distance)**Static:**

MEH 550W/650W	<15mV	+/-100% load, +/- full mains range
MDL, MDH	<0.05%	+/-100% load, +/- full mains range

Dynamic deviation depends on current slope resp. filter capacitors at load side only

Recovery time (40 m wire) 5V at load side, V drop < 2V**within +/-10% deviation****within +/-1% deviation**

MEH, MDH	<150ms	250ms
MDL	<150ms	320ms

Regulation timing adaptable to dynamic conditions (induced by cable length, voltage drops, sinker and filter capacities at load side)

DC output characteristics

Sense compensation range	limited to < 10V or nom voltage (except special versions)
Sense mode	closed loop and continuously controlling regulator to load
Floating Range PL508	>nominal output voltage for MEH, min. +/-10V for voltage ranges < 7V MEH and MDL

Noise and ripple

0.5 m wire (< 7V)	<10mV peak to peak	0-20 MHz
0.5 m wire (> 7V)	<15mV peak to peak	0-20 MHz
10 m wire	<3mV peak to peak	0-300 MHz

Conditions at load side: parallel (X) 330µF and 1µF ceramic, 100nF HF conducting to case (Y) each line

EMC compatibility

EN 61 000-6-3:2001	[RF emission]
EN 55 022:1998 + Corr:2001 + A1:2000 Class B	conducted noise
EN 55 022:1998 + Corr:2001 + A1:2000 Class B	radiated noise
EN 61 000-3-2:2001	harmonics
EN 61 000-3-3:1995 +Corr:1997 +A1:2001	flicker
EN 61 000-6-2:2001	[immunity]
EN 61 000-4-6:1996 + A1:2001	injected HF currents
EN 61 000-4-3:1996 + A1:1998 + A2:2001	radiated HF fields, "900MHz"
EN 61 000-4-4:1995 + A1:2001	burst
EN 61 000-4-5:1995 + A1:2001	surge
EN 61 000-4-11:1994 + A1:2000	voltage variations
EN 61 000-4-2:1995 + A1:1998 + A2:2001	ESD

Parameter

Emission:	CE EN 50081-1 (EN 55 022-B)
Immunity:	CE EN 50082-1 or 2
Operation temperature:	0...50°C without derating, storage: -30°C till 85°C
Temperature coefficient:	< 0.2% / 10K
Stability (condition const.):	<5mV or 0.1% within 24 h, <25mV or 0.3% within 6 months
Current limiting:	100% of nominal values, programmable to lower values via Interface or display tableau. In case of overcurrent: I _{lim} defines a constant current level, if status U _{min} set to 0V for the concerned channel, I _{max} defines the global trip off setpoint independant of status voltage window
Voltage rise:	Monotone and synchron. 50ms ramping (factory settings), other slope and different timing programmable
Voltage set:	discharge of output capacitors after DC off.

OV protection:	Factory setting to 125% of nominal values
Status control: DC Off (trip off):	within 3ms if >2% (default) deviation from nominal or programmed values , after overload, overheat (temperature limits 90/110°C heat sink, 70°C ambient), overvoltage, undervoltage , all trip off points processor controlled and programmable / disabling
DC Off / On, channel wise	By setting status Umin and output Voltage of selected channel both to 0V
Interlock input:	High level or open: All outputs DC off (optional feature)
Temperature limits:	90°C mains input, 110°C modules (heat sink), 70°C ambient internal
Efficiency:	Power module: 75% 2V/ -83% >5V/ -85% >12V/-90% >48V for 230VAC input voltage
M T B F:	>65,000 h (blower), electronics > 100,000 h at 40°C ambient

Product Data Sheet

PL512 Power Supply System: [Print Product Data Sheet](#)

Documentation

Manual: [PL506-PL512](#)

[RemoteControl](#)

Introduction: [WIENER Power Supplies intro](#)

Downloads

MUSEcontrol : [Download](#)

SNMP: [Download](#)

OPC-Server: [Download](#)

USB-to-IP: [Download](#)

Firmware MPRSE: [Download](#)

