

Radhound X/I

Hand-held Radiation Monitor

The Radhound X/I is an advanced hand-held survey meter with an internal dose rate detector.

Simple and easy to use

The menu on the Radhound X/I can be easily locked by the user to ensure only basic options are available, giving greater security and protection against accidental setting changes.

Alarm

The Radhound X/I has an adjustable alarm threshold. The sounder is loud and clear, and is suitable for use in many different environments. A symbol flashes on the display when in alarm.

Self test

The Radhound X/I automatically checks its health on turn on. It checks the high voltage, battery level, keyboard and sounder.

Peak mode

Records the maximum value seen since the last reset.

Scaler timer

The Radhound X/I has a scaler timer mode, allowing the integration of count for a preset time (or time to preset count). Additionally in dose rate mode, time to dose can be indicated.

Over range

Detector current measurement allows over range detection to prevent count saturation. Additionally the maximum count rate can be limited in the menu.

Long battery life

The Alkaline battery version uses two standard 1.5 V C-cells. Alternatively a Lithium Ion rechargeable version is available.

The screen has a battery level indicator in all counting modes.

Rugged case

The Radhound X/I case is waterproof to IP65, chemical resistant and can be safely wiped clean. A tough stainless steel case with impact resistant polymer ends means it will stand up to the rigours of daily use.



Specifications

Main modes of operation	Count (or dose rate), integrate/Scaler Timer, histogram (Count rate graph), Peak Value. Menu gives control of system parameters and multiple probe library.
Display	Large backlit LCD 70 mm x 40 mm Automatic backlight movement sensor – when instrument is picked up, the backlight comes on.
Displayed units	CPS, CPM, Sv/hr, μ Sv/hr, mSv/hr (R/hr, mR/hr, μ R/hr) Bq/cm ²
Response time	0.5 second response. Adjustable averaging time 5, 10, 15 seconds. Integration time adjustable up to 24 hours.
Operational parameters	High voltage adjustable from 300 - 1200 V User defined probe library up to 5 probes with adjustment of HV, gain, threshold, dead time, over range, probe name. Adjustable alarm levels. MHV Connector (other available on request).
Mechanical	Size: 165 mm x 115 mm x 59 mm excluding handle. Impact resistant, Waterproof to IP65. Weight typically 1.4 kg
Environmental	Operating temperature: -10°C to + 50°C Storage temperature: -25°C to +60°C In conformity with EMC directive (2004/108/EC), EN61326-1, EN61000-3-2, EN6100-3-3 Low Voltage Directive (2006/95/EC) Designed to meet IEC 60325-2006 and IEC 60846-2004 Nuclear Instrumentation Standards.
Power	On screen battery status indication. Uses 2 x 1.5 V Alkaline C-Cell (or optional Lithium Ion rechargeable). Battery life typically >40 hours of continuous use.
Options	Internal Lithium Ion Rechargeable Cell
Specifications	Internal Compensated GM Tube Range: 0.1 μ Sv/hr - 2 mSv/hr



Scientific House, The Henfield Business Park
Shoreham Road, Henfield, West Sussex, BN5 9SL
Tel: +44 (0)1273 497600, Fax: +44 (0)1273 497626
E-mail: info@southernscientific.co.uk, Web: www.southernscientific.co.uk