



# FLIR *identiFINDER™ R100*

## *Personal Radiation Detector*

The FLIR identiFINDER R100 is a personal radiation detector (PRD) in a belt-worn, rugged form factor. It delivers immediate threat alarms to front-line responders and automatically generates a dose-rate report providing continuous, situational awareness to central command. Every R100 features integrated Bluetooth® Smart technology that connects directly to a smart device, enabling networking. The R100 is IP67 certified to protect against dust and water immersion up to 1m. It meets the 1.5m-drop criteria required by ANSI N42.32, a key performance standard for alarming PRDs deployed in harsh responder environments. The R100 joins the industry-leading identiFINDER product family, offering a complete range of first responder radiation security solutions, from threat detection to threat identification.

### **BELT-WORN PRD WITH INTEGRATED BLUETOOTH**

*Continuous Front-Line Situational Awareness*

- Features integrated Bluetooth Smart technology
- Mobile apps display real-time output and record and send dose rate and geotag
- Eliminates information blind spots and increases operator safety

### **DUNKABLE AND DEPENDABLE**

*Supports everyday use in challenging, harsh environments*

- IP67-rated to protect against dust and immersion in water up to 1m
- Meets the 1.5m-drop criteria required by the ANSI N42.32 PRD standard
- Clear, backlit memory display outperforms the competition in every lighting condition


### **SOLUTIONS FROM THREAT DETECTION TO IDENTIFICATION**

*Fully integrated product family, from PRD to premium-class RIID (radio-isotope identification device)*

- Shared automated report format across all identiFINDER models
- Intuitive user interface shared across all identiFINDER models
- Common training across all identiFINDER models minimizes total cost of ownership

## Specifications

<b>identiFINDER R100</b>	
Technology	Personal Radiation Detector (PRD)
Gamma (G-M)	Energy Compensated Geiger-Müller Tube
Energy Range (Gamma)	25keV - 3MeV; energy compensated dose rate 60keV - 1.5MeV
Gamma Sensitivity	17cps / mR/h
Dose Rate Range (Cs-137)	50µrem/h (0.5µSv/h) to 1 rem/h (10mSv/h)
Dose Rate / Accuracy (Cs-137)	±20%
Dose Rate Units	rem/h or Sv/h; user adjustable
Service Interval	Recommended five year factory maintenance interval; annual dose rate calibration interval
<b>SAMPLING &amp; ANALYSIS</b>	
Sample Introduction	Absorption of EM gamma emissions
Threats	Detects gamma radiation emitted from natural occurrences in the environment, special nuclear material, industrial, or medical material
Compliance	Meets the 1.5m drop criteria required by ANSI N42.32, fully compliant with ANSI N42.33
Sampling & Analysis	Continuous
<b>SYSTEM INTERFACE</b>	
Display	Transflective Monochrome LCD
Alerts	Visible (front and top LEDs), audible, and haptic (vibration)
Localization	Language translation available worldwide
Communication	USB 2.0; micro-AB socket; integrated Bluetooth® up to 10m range
Software	On-board webserver software
<b>POWER</b>	
Input Voltage	4.5V to 5.5V USB micro-AB socket
Battery Specs	Two replaceable 1.5V AA Alkaline batteries; operational life >125h
Cold Start Time	<2 mins from cold start
<b>Environmental</b>	
Operating Temp	-4 to 122 °F (-20 to 50 °C)
Operating Humidity	93% RH @ 35 °C non-condensing
Storage Temp	14 to 95 °F (-10 to 35 °C)
<b>PHYSICAL FEATURES</b>	
Dimensions (L x W x H)	5.3 x 2.2 x 1.5 in. (13.5 x 5.5 x 3.7 cm)
Weight	0.55 lb (0.25 kg)
Enclosure & Protection	Plastic with rubber overmold; protection rating IP67 according to IEC 60529



Dose Rate Mode



Scientific House, The Henfield Business Park  
 Shoreham Road, Henfield  
 West Sussex BN5 9SL  
 Tel: +44 (0)1273 497600  
 Fax: +44 (0)1273 497626  
 E-mail: [info@southernscientific.co.uk](mailto:info@southernscientific.co.uk)  
 Web: [www.southernscientific.co.uk](http://www.southernscientific.co.uk)

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2016 FLIR Systems, Inc. All rights reserved. 16-0901