

## MOBILE RADIATION MONITOR

RADIATION MONITOR DEPLOYED  
IN VAN

STATIONARY OR MOBILE  
INSPECTION

GAMMA AND NEUTRON  
RADIATION DETECTION

FLEXIBLE INSPECTION  
OPERATIONS

### MARKETS


- Airports
- Critical Infrastructure
- Aviation
- Event Security



Cut-away view of the TSA MD134 mounted in a van for mobile screening. (Van is not included.)



Detector



Controller

THE TSA MD134 IS DESIGNED TO AUTOMATICALLY SCAN VEHICLES OR CONTAINERS WITHOUT THE NEED FOR FREQUENT CALIBRATION.

The system can be stationary to scan vehicles as they drive by or it can be mounted in a vehicle and driven past items to be scanned.

### ADVANCED OPERATIONAL FEATURES

When the system is powered up, it acquires an initial background count typically within 120 seconds. The TSA MD134 can be put in occupancy mode two different ways, sensor activated or constant. When occupancy is activated the system starts comparing the current count to the most recent background data. Alarm comparisons are made every 200ms. If the count exceeds the alarm level, both audible and visual alarms will be triggered. The system monitors itself and indicates low and high background conditions.

### FLEXIBLE DETECTION OPTIONS

The TSA MD134 is available in three configurations; Gamma, Neutron or a combination of Gamma and Neutron detection. Gamma provides detection of ionizing radiation and Neutron provides detection of Special Nuclear Materials (SNM) while the combined Gamma and Neutron provides the most powerful detection capabilities for radioactive isotopes even in shielded materials.

### INTERFACE FEATURES

The TSA MD134 includes TSA RAVEN™ communications software designed to both capture and view data and video images relating to a radiological detection incident.



# TSA MD134

# Rapiscan<sup>®</sup> systems

An OSI Systems Company

## PHYSICAL SPECIFICATIONS

Dimensions:	Length: 6,366 mm (250.6 in.) Length with Conveyors: 8,496 mm (334.5 in.) Width: 3,379 mm (133.0 in.) Height: 3,181 mm (125.2 in.)
Sensitivity	Gamma: Will detect 1,000g of 235U (HEU) or 10g of 239Pu in 20 uR/hr background at a passage speed of five mph (8km/h), at a distance of 39 in. (1 m). Neutron*: Will detect less than 200g of plutonium in a shielded container that reduces the gamma flux to 1% of the unshielded gamma flux.
Detectors	Gamma: Two, 48 h x 12 w x 1.5 d in. (121 x 30 x 3.8 cm) organic plastic scintillator detectors per skid; provide approximately 1,728 in <sup>3</sup> (28 liters) of detector volume. Standard Neutron*: Four, 2 in. diameter x 36 in. (5 x 91 cm) He <sup>3</sup> tube. High Sensitivity Neutron*: Eight, 2 in. diameter x 36 in. (5 x 91 cm) He <sup>3</sup> tube.
Alarm Indication	Alarms are indicated on the External Alarm Box and the laptop or PC that is monitoring the system.
Communications	Serial Port and Ethernet
Display	Alphanumeric LCD, 4 lines x 16 characters.
Charging Requirements	90-250, 47-63Hz or 12VDC from host vehicle.
Battery Life	16 hours of continuous operation.
Dimensions	66.4 in h x 60 w x 25 in d in. (168.5 cm x 152.5 x 63.5 cm) per skid.
Weight	500 lbs (227 kg) per skid.
Environmental	-4° to 122° F (-20° to 50°C); designed for sheltered areas.

## STANDARD FEATURES

- Programmable Detection Parameters
- Audio and Visual Indicators
- Relay Outputs for User Interface
- Universal Power Supply
- Ethernet Connectivity
- Wireless Output Capabilities
- Battery Backup
- Controller Mounting Options
- External Alarm Box
- TSA RAVEN™ Software

## DEFINITIONS

- Gamma Detection - For the detection of ionizing radiation.
- Neutron Detection - Typically used to detect Special Nuclear Materials (SNM).
- Gamma and Neutron Detection - For full spectrum detection capabilities.

## OPTIONS

- Wireless Communications
- Survey and Mobile Mode
- External Alarm Box

With continual development of our products Rapiscan Systems reserves the right to amend specifications without notice. Product pictures are for general reference. Please note that due to US laws and regulations, not all Rapiscan products are available for sale in all countries without restriction. Please contact your Rapiscan Systems sales representative for more information.

\*For neutron detection please contact your sales representative to determine availability and quantity of He<sup>3</sup> tubes.

### AMERICAS, CARIBBEAN

2805 Columbia Street  
Torrance,  
California  
90503  
UNITED STATES of AMERICA

Tel: +1 310-978-1457  
Fax: +1 310-349-2491

### EUROPE, MIDDLE EAST, AFRICA

X-Ray House  
Bonehurst Road  
Salfords  
Surrey RH1 5GG  
UNITED KINGDOM

Tel: +44 (0) 870-7774301  
Fax: +44 (0) 870-7774302

### ASIA

240 Macpherson Road  
#07-01 Pines Industrial Building  
Singapore  
348574  
SINGAPORE

Tel: +65-6846-3511  
Fax: +65-6743-9915



Rapiscan Systems is ISO 9001:2008 Certified

[sales@rapiscansystems.com](mailto:sales@rapiscansystems.com)  
[www.rapiscansystems.com](http://www.rapiscansystems.com)