

CRC®-55tR Dose Calibrator

The new Capintec CRC®-55tR Dose Calibrator provides the speed and accuracy you need to measure and prepare doses with the reliability and performance you expect from Capintec. The CRC®-55tR's design includes a menu driven, color touch screen interface that is easy to learn and use.

The ion chamber is one of Capintec's time-tested, high pressure well designs capable of measuring a dose as high as 6 Ci (250 GBq) with high accuracy.

Additional features such as USB/PC Communications, printer capabilities, ethernet software upgrades, plug and play chamber and expanded remote capabilities make the CRC®-55tR integral in improving your department's efficiency.

The innovative functional design of the CRC®-55tR allows for a large, easy-to-read display that indicates Nuclide Name, Number, Activity, Unit of Measure and Calibration Number.

Entering data through the custom touch screen interface is fast and includes 28 programmable keys. The user can select from 80 nuclides by simply selecting the nuclide symbol on the touch screen interface.

Other capabilities include storage of reference sources in memory that automatically decay correct for today's time and date. Automated quality control tests and self-diagnostics are built-in with automatic zero and background subtraction making the CRC®-55tR exceptionally easy to use. An optional printer enables the CRC®-55tR to print full size records and patient tickets with peel off labels for vial and syringe identification.

- 8" color VGA touch screen display
- Chamber plug-and-play capability
- Chamber and remote can be placed 100 feet from the readout unit
- Selection of Nuclide and Daily Test can be done with the remote
- On screen display of Nuclide Name, Number, Activity, Unit of Measure and Calibration Number
- Large character, high visibility display
- Over 80 Nuclides with half-lives in memory
- Full alpha numeric touchpad
- Built-in dose calibration, quality control and self diagnostics
- Automated QC including constancy and linearity programs
- Compatible with Nuclear Medicine Management Systems
- Optional printer for full size NRC records and patient labels for syringes and vials.
- Optional intelligent programmable remote display indicating Nuclide, Activity and Unit of Measure, and perform daily test
- Optional second chamber
- USB/PC Communications
- Software upgrade via ethernet interface
- USB printer capability

Chamber Dimensions

- Height: 43.8cm (17.25in)
- Diameter: 17.2cm (6.76in)
- Weight: 13.6kg (30lb)
- Well Diameter: 6.1cm (2.4in)
- Well Depth: 25.4cm (10.0in)
- Cable Length¹: 3.7m (12ft)

Console Dimensions

- Height: 42cm (9.5in)
- Width: 23cm (9.0in)
- Depth: 27cm (10.5in)
- Weight: 3.4kg (7.5lb)

Cables

- Power¹: 1.8m (6ft)
- Printer: 1.8m (6ft)

¹: Longer cables are available. Consult factory.



CRC[®]-55tR Dose Calibrator

Ionization Chamber

- Type: Thin wall, deep well, high pressure
- Fill Gas: 12 atm Ultra Pure Argon

Measurement Range

- Type: Auto Ranging
- Activity: 250 GBq (6 Ci), max.
- Resolution: .001 MBq (.01 μ Ci), max.

Display Screen

- Type: 8" VGA LCD color touch screen display
- Format: Direct reading in Bq or Ci
- Bq/Ci Reading: User selectable or fixed
- Values Displayed: Nuclide name (Atomic symbol, Mass number), calibration number

Electrometer

- Accuracy: Better than $\pm 2\%$
- Linearity: Within $\pm 2\%$
- Response Time: Within 2 sec., 4 to 16 sec. for very low activity samples (user selectable average period)

Repeatability of Measurement

- Repeatability: Within $\pm 1\%$ within 24 hours, during which time the calibrator is on all the time.

Tests

- Diagnostics: Full test of program, system memories
- Daily: Auto Zero, Auto Background Adjust, Data Check, Accuracy and Constancy, Voltage Test
- Enhanced: Linearity, Geometry, Strip QC

Nuclear Data

- Nuclide Keys: 28 programmable keys
- System Memory: Over 80 nuclides (cal number and half-life)

Standard Source Data

- System Memory: Co-57, Co-60, Ba-133, Cs-137 Standard Sources

Molybdenum-99 Assay

- Methods: Canisters of CAPMAC
- Measured Values: Mo-99 elution, Tc-99m, Tc-99m/Mo-99 Ratio

PC Port

- Interface: RS-232 & USB
- Compatibility: Standard Nuclear Medicine Management Systems
- Ethernet interface

Printer (Optional)

- Interface: RS-232 and USB
- Type: Epson Roll, Epson Slip or Okidata full size dot matrix
- Printing Options: Full size test reports. Measured results on tickets.

Power Requirements

- 100-240 VAC (50/60Hz) 90 MA

Optional Components



CRC Auxiliary Display:
Item #5130-2224



Epson Roll Printer:
Item #5430-0058




Epson Ticket Printer:
Item #5430-0100




CRP-200 Dose Tickets & Labels:
Item #7120-1199



CAP-MAC-2:
Item #5130-0108



Molly Assay Canister:
Item #5130-0006



Dipper:
Item #7300-2005



Chamber Well Insert:
Item #7300-2004



Scientific House, The Henfield Business Park,
Shoreham Road, Henfield, West Sussex, BN5 9SL
Tel: +44 (0)1273 497600
Email: info@southernscientific.co.uk